AQUILA DN15 (PHASED OUT)

Single-Jet Meter



APPLICATION

AQUILA is a single jet meter specifically designed for measuring cold water in main metering market.

2015

AQUILA is characterised by its accurate metering capability, particularly with low flow rates, its ruggedness and its resistance to clogging. Its profiled inlet nozzle makes it immune to disturbances in the piping before or after the meter. Developed within the framework of the MID, AQUILA complies with the European regulations and holds a sanitary conformity certificate.

Modular, AQUILA may be fitted at any time with an IZAR clip-on module, converting it into a communicating meter ready for mobile or fixed (radio/wired) network reading.

FEATURES

-) DN 15
- ▶ Q3=2.5 m³/h
- MID approval up to R=200H & R=40V
- Starting flow rate: < 6 l/h</p>
- Cold water
- Composite body
- Integrated plastic inlet filter
- Tamper-proof ring

AQUILA DN15 (PHASED OUT)

Single-Jet Meter

METROLOGICAL DATA

| Nominal diameter | DN | mm | 15 | 15 |
|--|--------------------------------|------|----------|----------|
| Length | L | mm | 110 | 115 |
| Nominal flowrate | Q₃ | m³/h | 2.5 | 2.5 |
| R standard* | Q ₃ /Q ₁ | | 200H-40V | 200H-40V |
| Starting flowrate horizontal | | l/h | < 6 | < 6 |
| Minimum flowrate horizontal | Q ₁ | l/h | 12.5 | 12.5 |
| Transition flowrate horizontal | Q ₂ | l/h | 20 | 20 |
| Minimum flowrate vertical | Q ₁ | l/h | 62.5 | 62.5 |
| Transition flowrate vertical | Q_2 | l/h | 100 | 100 |
| Maximum flowrate | Q ₄ | m³/h | 3.125 | 3.125 |
| Head loss at Q₃ | | bar | 0.61 | 0.61 |
| Head loss at Q4 | | bar | 0.95 | 0.95 |
| Kvs (deltaP=Q ² /Kvs ²) | | | 3.201 | 3.201 |

* other values on request - H=horizontal installation position / V=vertical installation position.


APPROVAL


| | AQUILA DN15 |
|---------------------|--------------------------------|
| MID approval | LNE-29388 C3 type |
| Standards | EN 14154 ISO 4064 OIML R49 |
| Sanitary conformity | ACS |

TEMPERATURE AND PRESSURE

| | | | AQUILA DN15 |
|-------------------------------|----|-----|-------------|
| Water temperature | | °C | +0.1 +50 |
| Ambient operating temperature | | °C | +1 +55 |
| Storage temperature | | °C | -10 +55 |
| Nominal pressure | PN | bar | 16 |

DIMENSIONS





AQUILA DN15 - side view

AQUILA DN15 - top view


| Nominal diameter | DN | mm | 15 | 15 |
|--------------------|----|------|-----------|-------------|
| Length | L | mm | 110 | 115 |
| Width | В | mm | 94 | 94 |
| Total height | H1 | mm | 92 | 92 |
| Height | h | mm | 22 | 22 |
| Thread connections | G | inch | 3/4" | 3/4" - 7/8" |
| Body | | | composite | composite |
| Weight | | kg | 0.430 | 0.430 |

Diehl Metering GesmbH · Hainburger Strasse 33 · A-1030 Wien · Austria Phone: +43 (0)1 716 70-0 · Fax: +43 (0)1 716 70-12 · metering-austria-info@diehl.com · www.diehl.com/metering Subject to technical adjustments

AQUILA DN15 (PHASED OUT)

Single-Jet Meter

PRECISION CURVE



This technology doesn't require any straight length.

OPTION

- Non-return valve